

HONDA ST PAN EUROPEAN ST 1100 PAN EUROPEAN (1987-1995)



ENGINE/TRANSMISSION

Capacity: 3,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 10W-40	Expulsa 10W-40

Change every 12000 km/ 12 months

SHAFT DRIVE

Capacity: 0,13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 12000 km, change every 36000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 18000 km/ 24 months

COOLING SYSTEM

Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 6000 km/ 6 months, change every 18000 km/ 24 months

FRONT FORK

Capacity: 0,44 liter (Left), Capacity: 0,39 liter (Right)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

HONDA ST PAN EUROPEAN ST 1100 PAN EUROPEAN (1987-1995)



information contained herein is subject to changes without notification.