

HONDA TRX TRX 250 (1985-1987)**ENGINE/TRANSMISSION**

Capacity: 2,5 liter (Service fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Change every 1000 km/ 12 months/ 100 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 1000 km/ 12 months/ 100 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Change every 150 km/ 20 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

*Change every 150 km/ 20 hours***DIFFERENTIAL REAR**

Capacity: 100 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

*Change every 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

HONDA TRX TRX 250 (1985-1987)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.