PRODUCT RECOMMENDATION

HONDA TRX TRX 300 FW BIG RED 4X4
(1987-2000)

ENGINE/TRANSMISSION
Capacity: 2,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Expulsa RR 10W-40	**Expulsa 10W-40**	**HDX 10W-40**
Change every 3 months/ 240 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 3 months/ 240 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Expulsa RR 10W-40	**Expulsa 10W-40**	**HDX 10W-40**
Change every 40 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 40 hours		

GEAR CASE FRONT
Capacity: 200 CM3

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Expulsa RR 10W-40	**Expulsa 10W-40**	**HDX 10W-40**
Change every 24 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 24 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HONDA TRX TRX 300 FW BIG RED 4X4
(1987-2000)

HUB REDUCTIONS FRONT
Capacity: 190 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**SP Gear 1071**	

Change every 24 months

HUB REDUCTIONS REAR
Capacity: 90 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**SP Gear 1071**	

Change every 24 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367