

# HONDA TRX TRX 420 FE/FPE ES 4X4 / FOURTRAX RANCHER (2010-2013)

**ENGINE/TRANSMISSION**

Capacity: 3,1 liter (Dry fill), Capacity: 2,8 liter (Service fill), Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 1000 km/ 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-40</b>	

*Change every 1000 km/ 100 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 150 km/ 20 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 5W-40</b>	

*Change every 150 km/ 20 hours***DIFFERENTIAL FRONT**

Capacity: 230 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>

*Change every 24 months***DIFFERENTIAL REAR**

Capacity: 75 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>

*Check every each race, change every 24 months*

# HONDA TRX TRX 420 FE/FPE ES 4X4 / FOURTRAX RANCHER (2010-2013)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Change every 24 months

## COOLING SYSTEM

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.