HONDA VF VF 750 C/CD (1994-2003)



ENGINE/TRANSMISSION Capacity: 3,8 liter (Dry fill), Capacity: 3,1 liter (Service fill), Filter capacity: 0,1 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50		
Change every 12800 km				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		
Change every 12800 km				
USE		CLIMATE		
First change only		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50		
Change every 1000 km				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		
Change every 1000 km		•		

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Charles war C400 lime charge a view 40000 lime (A months				

Check every 6400 km, change every 19200 km/24 months

COOLING SYSTEM Capacity: 2,4 liter, Capacity: 0,4 liter (Reserve tank)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Coolant -38 Organic NF	Coolant -26				
Check every 12800 km, change every 38400 km					

HONDA VF VF 750 C/CD (1994-2003)



FRONT FORK Capacity: 0,52 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		
Check every 12800 km	6	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.