HONDA VTR VTR 1000 F FIRESTORM (1997-2006)



ENGINE/TRANSMISSION Capacity: 3,9 liter, Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
HDX 40		
Change every 12000 km/ 12 months		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50
Change every 12000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40
Change every 12000 km/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 12000 km/ 12 months		

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check over 5000 km/ 5 menths, change over 12000 km/ 24 menths				

Check every 6000 km/ 6 months, change every 18000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 6000 km/ 6 months, change every 18000 km/ 24 months

HONDA VTR VTR 1000 F FIRESTORM (1997-2006)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Coolant -26	

Check every 12000 km/ 12 months, change every 36000 km/ 24 months

FRONT FORK Capacity: 0,45 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 12000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.