

**HONDA XR XR 400 R (1995-2003)****ENGINE/TRANSMISSION**

Capacity: 1,8 liter, Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 6000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 24 months***FRONT FORK**

Capacity: 0,47 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 1600 km, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.