

**HUSABERG FE FE 650 E (2004-2008)****ENGINE/TRANSMISSION**

Capacity: 1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 15 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 15 hours*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 3 hours*

USE	CLIMATE
First change only	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 3 hours***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1***Check every 15 hours, change every 12 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

**HUSABERG FE FE 650 E (2004-2008)****COOLING SYSTEM**

Capacity: 1-1,3 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 15 hours***FRONT FORK****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Fork Oil RR 5***Change every 15 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*