HUSABERG FS FS 650/6 (2005-2008)



ENGINE/TRANSMISSION Capacity: 1 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 15 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 15 hours	
USE	CLIMATE
First change only	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 3 hours	
USE	CLIMATE
First change only	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 3 hours	

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		
Observations 45 hours about a supplied		

Check every 15 hours, change every 12 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUSABERG FS FS 650/6 (2005-2008)



COOLING SYSTEM Capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 15 hours			

FRONT FORK	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 5	
Change every 15 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.