

HUSQVARNA SMR SMR 630 (2003-2006)**ENGINE/TRANSMISSION**

Capacity: 1,5 liter (Initial fill), Capacity: 1,25 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-40***Change every 500 km/ 2 races***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 5 hours, change every 15 hours***COOLING SYSTEM**

Capacity: 1,1-1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****FRONT FORK****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32***Change every 15 hours***SHOCK ABSORBER REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.