HUSQVARNA TE TE 250 R (2013-2013)



ENGINE/TRANSMISSION Capacity: 0,9 liter, Filter capacity: 0,05 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 5000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 1000 km		
USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 10 hours		
USE		CLIMATE
Competition, first service only		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 3 hours		
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 5000 km, change every 1000	0 km	
USE		CLIMATE
Competition		Moderate

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 40 hours, change every 80 hours

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

HUSQVARNA TE TE 250 R (2013-2013)



HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 5000 km, change every 10000 km				
USE		CLIMATE		
Competition		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 40 hours, change every 80 hours

COOLING SYSTEM Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 5000 km		
USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 5 hours

FRONT FORK

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Fork Oil RR 5				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.