

ENGINE/TRANSMISSION

Capacity: 1,4 liter, Filter capacity: 0,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 4 hours, change every 40 hours

HYDRAULIC CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 32				
Charle avery 4 hours aborre avery 40 hours				

Check every 4 hours, change every 40 hours

COOLING SYSTEM Capacity: 1,1-1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

Check every 8 hours

FRONT FORK	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 16 hours	

SHOCK ABSORBER REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.