

**HUSQVARNA WR WR 125 (2010-2013)****ENGINE**

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION 6**

Capacity: 0,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

*Change every 3000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

*Change every 1000 km*

| USE         | CLIMATE  |
|-------------|----------|
| Competition | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

*Change every 8 hours*

| USE                             | CLIMATE  |
|---------------------------------|----------|
| Competition, first service only | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

*Change every 4 hours*

**HYDRAULIC BRAKE SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 10000 km*

| USE         | CLIMATE  |
|-------------|----------|
| Competition | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Check every 4 hours, change every 40 hours*

**HUSQVARNA WR WR 125 (2010-2013)****COOLING SYSTEM**

Capacity: 1,1-1,3 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 1500 km*

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Competition                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 4 hours***FRONT FORK**

We are unable to give a standard recommendation for this component. Please contact our service department.

**SHOCK ABSORBER REAR**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Fork Oil RR 5</b>     |  |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*