

**HYTRACK HY 150 HY 150 SX****ENGINE 157QMJ**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 3 months/ 30 hours***FINAL REDUCTION**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 100 hours/ 12 months***GEARBOX 1/1**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 100 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 24 months/ 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.