

# INDIAN CHIEF/VINTAGE CHIEF DELUXE (2009-2010)



**ENGINE 105**  
Capacity: 3,31 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 8000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 800 km*

| USE                | CLIMATE  |
|--------------------|----------|
| Second change only | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 4000 km*

**PRIMARY DRIVE**  
Capacity: 0,59-0,65 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 8000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 800 km*

# INDIAN CHIEF/VINTAGE CHIEF DELUXE (2009-2010)



**TRANSMISSION 6**  
Capacity: 0,6-0,72 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2           |
|--------------------------|------------------------------------|
| <b>SP Gear 1011</b>      | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Change every 8000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2           |
|--------------------------|------------------------------------|
| <b>SP Gear 1011</b>      | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Change every 800 km*

**HYDRAULIC BRAKE SYSTEM FRONT**  
Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |
|----------------------------------|---------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |

*Change every 16000 km/ 24 months*

**HYDRAULIC BRAKE SYSTEM REAR**  
Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |
|----------------------------------|---------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |

*Change every 16000 km/ 24 months*

**HYDRAULIC CLUTCH SYSTEM**  
Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |
|----------------------------------|---------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |

*Change every 16000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*