

KAWASAKI KVF (BRUTE FORCE) BRUTE FORCE 750 4X4 /EPS KVF 750 G/H/J/LCF > (2012 AND AFTER)

**ENGINE/TRANSMISSION**

Capacity: 2,4 liter (Dry fill), Capacity: 2 liter (Service fill), Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 1700 km/ 3 months/ 100 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 1700 km/ 3 months/ 100 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 100 km/ 10 hours

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 100 km/ 10 hours

KAWASAKI KVF (BRUTE FORCE) BRUTE FORCE 750 4X4 /EPS KVF 750 G/H/J/LCF > (2012 AND AFTER)

**DIFFERENTIAL FRONT**

Capacity: 0,4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Change every 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 km/ 10 hours

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

*Change every 100 km/ 10 hours***DIFFERENTIAL REAR**

Capacity: 0,72 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 3000 km/ 6 months, change every 24 months

KAWASAKI KVF (BRUTE FORCE) BRUTE FORCE 750 4X4 /EPS KVF 750 G/H/J/LCF > (2012 AND AFTER)

**COOLING SYSTEM**

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.