

# KAWASAKI KX / KXF KX 85 KX85-A1 > A9F

(2001-2009)



## ENGINE

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Tornado**

### PRODUCT RECOMMENDATION 2

**Scoosynth**

### PRODUCT RECOMMENDATION 3

**Maestrol**

## TRANSMISSION 6

Capacity: 0,7 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

### PRODUCT RECOMMENDATION 2

**Expulsa 10W-40**

### PRODUCT RECOMMENDATION 3

**HDX 10W-40***Change every 3 races*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

### PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 24 months*

## COOLING SYSTEM

Capacity: 0,67 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 1 each race*

# KAWASAKI KX / KXF KX 85 KX85-A1 > A9F

(2001-2009)

**FRONT FORK**

Capacity: 315 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Fork Oil RR 5***Change every 5 races*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Fork Oil RR 5***Change every 2 races*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*