

# KAWASAKI NINJA EX/ZX/BX NINJA 650R

## EX650-C9F/CAF/CBF > (2008-2011)

**ENGINE/TRANSMISSION**

Capacity: 2,4 liter (Dry fill), Capacity: 1,9 liter (Service fill), Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 12000 km/ 12 months*

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 24 months***COOLING SYSTEM**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 36 months***FRONT FORK**

Capacity: 474-485 CM3 (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 10</b>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.