

KAWASAKI NINJA ZX-6 ZX600 / ZX636

NINJA ZX-6R ZX636-B2 (2004-2004)



ENGINE/TRANSMISSION

Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Change every 12000 km/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Change every 1000 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 6000 km/ 1 months, change every 24000 km/ 24 months

COOLING SYSTEM

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24000 km/ 24 months

FRONT FORK

Capacity: 482 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.