

KAWASAKI VULCAN / LTD EN / VN VN

VULCAN 1500 CLASSIC VN1500-E1 > E3

(1998-2000)

**ENGINE/TRANSMISSION**

Capacity: 4 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 6000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

*Change every 1000 km***SHAFT DRIVE**

Capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 36000 km

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	SP Gear 1071

Change every 36000 km

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 km

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	SP Gear 1071

Change every 1000 km

KAWASAKI VULCAN / LTD EN / VN VN

VULCAN 1500 CLASSIC VN1500-E1 > E3

(1998-2000)

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24000 km/ 24 months

COOLING SYSTEM

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24000 km/ 24 months

FRONT FORK

Capacity: 465 CM3 (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

Change every 24000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.