Change every 1000 km

KAWASAKI VULCAN / LTD EN / VN VN VULCAN 1700 VOYAGER (ABS) VN1700-A9F/AAF/ABF > (2009 AND AFTER)



ENGINE/TRANSMISSION Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40		
Change every 12000 km/ 12 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 24000 km/24 months		,

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	aax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24000 km/ 24 months			

COOLING SYSTEM Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 36000 km/ 36 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.