

KTM 150 150 XC (2011-2012)**ENGINE**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Tornado

PRODUCT RECOMMENDATION 2

Maestrol**TRANSMISSION 6**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50*Change every 20 hours/ 140 liter consumed fuel***HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1

PRODUCT RECOMMENDATION 2

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid-S DOT 4*Change every 12 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 1,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26**FRONT FORK**

Capacity: 195 CM3 (cartridge each), Capacity: 360 CM3 (each leg without cartridge)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Fork Oil RR 5*Change every 20 hours**The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.*

KTM 150 150 XC (2011-2012)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.