PRODUCT RECOMMENDATION

KTM 250 250 SX-F (2005-2006)

ENGINE/TRANSMISSION
Capacity: 1,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		

Change every 10 hours/ 70 liter consumed fuel

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 10 hours/ 70 liter consumed fuel

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		

Change every 3 hours/ 20 liter consumed fuel

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 3 hours/ 20 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 10 hours/ 1 race/ 70 liter consumed fuel, change every 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 3 hours/ 20 liter consumed fuel

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KTM 250 250 SX-F (2005-2006)

HYDRAULIC CLUTCH SYSTEM Brembo

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 10 hours/ 1 race/ 70 liter consumed fuel, change every 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 3 hours/ 20 liter consumed fuel

HYDRAULIC CLUTCH SYSTEM Magura

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 1 race/ 70 liter consumed fuel/ 10 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 3 hours/ 20 liter consumed fuel

FRONT FORK

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367