

**KTM 400 400 EXC (2008-2010)****ENGINE**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 100 liter consumed fuel/ 15 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 100 liter consumed fuel/ 15 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 3 hours/ 20 liter consumed fuel*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 3 hours/ 20 liter consumed fuel*

**KTM 400 400 EXC (2008-2010)****TRANSMISSION 6**

Capacity: 0,9 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-50</b>		

*Change every 20 hours/ 140 liter consumed fuel*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-40</b>		

*Change every 20 hours/ 140 liter consumed fuel*

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-50</b>		

*Change every 3 hours/ 20 liter consumed fuel*

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-40</b>		

*Change every 3 hours/ 20 liter consumed fuel***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 5.1</b>		

*Check every 1 race/ 100 liter consumed fuel/ 15 hours, change every 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 5.1</b>		

*Check every 3 hours/ 20 liter consumed fuel*

**HYDRAULIC CLUTCH SYSTEM** Brembo

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 5.1</b>		

*Check every 1 race/ 100 liter consumed fuel/ 15 hours, change every 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 5.1</b>		

*Check every 3 hours/ 20 liter consumed fuel*

**HYDRAULIC CLUTCH SYSTEM** Magura

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 0,95 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 1 race/ 100 liter consumed fuel/ 15 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 3 hours/ 20 liter consumed fuel*

**FRONT FORK**

Capacity: 626 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Fork Oil RR 5</b>		

*Change every 15 hours*

**SHOCK ABSORBER REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

# KTM 400 400 EXC (2008-2010)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*