KTM 450 450 SMR (2014-2015)



ENGINE/TRANSMISSION Capacity: 1,35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 10 hours/ 70 liter consumed fuel			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 1 hours/ 7 liter consumed fuel			

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

	CLIMATE
	Moderate
RODUCT RECOMMENDATION 2	
Coolant -26	

Change every 24 months

FRONT FORK

Capacity: 195 CM3 (cartridge each), Capacity: 380 CM3 (each leg without cartridge)

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

KTM 450 450 SMR (2014-2015)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.