KTM 65 / 85 / 105 SX 85 SX (2004-2005)



ENGINE CR 85				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Tornado	Maestrol			

TRANSMISSION 6 Capacity: 0,35 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	

Check every 2000 km/20 hours, change every 4000 km/12 months

HYDRAULIC BRAKE SYSTEM		
CLIMATE		
Moderate		

Check every 1000 km/ 10 hours, change every 4000 km/ 12 months

HYDRAULIC CLUTCH SYSTEM Brembo			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 5.1			

Check every 1000 km/ 10 hours, change every 4000 km/ 12 months

HYDRAULIC CLUTCH SYSTEM Magura

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 1000 km/ 10 hours, cha	ange every 4000 km/ 12 months	

KTM 65 / 85 / 105 SX 85 SX (2004-2005)



FRONT FORK				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Fork Oil RR 5				
Check every 1000 km/ 10 hours, change every 4000 km/ 12 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.