

KTM 950 950 SUPERMOTO (2005-2009)**ENGINE/TRANSMISSION 950 LC8**

Capacity: 3 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 7500 km/ 12 months*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 7500 km/ 12 months*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 1000 km*

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Arctic |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1*Check every 7500 km/ 12 months, change every 15000 km/ 24 months*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1*Check every 1000 km***HYDRAULIC CLUTCH SYSTEM Brembo**

We are unable to give a standard recommendation for this component. Please contact our service department.

KTM 950 950 SUPERMOTO (2005-2009)**COOLING SYSTEM**

Capacity: 2,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Change every 15000 km/ 24 months***FRONT FORK****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 5***Change every 15000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.