

KTM 990 990 ADVENTURE BAJA (2013-2013)**ENGINE/TRANSMISSION**

Capacity: 3 liter

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 1000 km*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1000 km*

USE	CLIMATE
Second change only	Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 7500 km/ 12 months*

USE	CLIMATE
Second change only	Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 7500 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1

PRODUCT RECOMMENDATION 2

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid-S DOT 4*Change every 15000 km/ 24 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

KTM 990 990 ADVENTURE BAJA (2013-2013)**COOLING SYSTEM**

Capacity: 2,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 30000 km/ 48 months***FRONT FORK WP 4860 MXMA PA**

Capacity: 655 CM3

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 5***Check every 7500 km/ 12 months***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 5***Check every 1000 km***SHOCK ABSORBER REAR WP PDS 5018 DCC PA**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.