## KTM 990 990 ADVENTURE (2009-2012)



ENGINE/TRANSMISSION Capacity: 3 liter	
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 1000 km	
USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 1000 km	
USE	CLIMATE
Second change only	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 7500 km/ 12 months	
USE	CLIMATE
Second change only	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 7500 km/ 12 months	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 15000 km/24 month	78			

## **HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

## KTM 990 990 ADVENTURE (2009-2012)



COOLING SYSTEM Capacity: 2,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 30000 km/ 48 months	·

USE	CLIMATE
	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 5	

Check every 7500 km/ 12 months

USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Fork Oil RR 5				

Check every 1000 km

## **SHOCK ABSORBER REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.