KTM 990 990 SUPERMOTO R (2013-2013)



ENGINE/TRANSMISSION Capacity: 3 liter	
USE	 CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 7500 km/ 12 months	
USE	 CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 7500 km/ 12 months	
USE	 CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 1000 km	
USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 1000 km	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 7500 km/ 12 months, change every 15000 km/ 24 months

Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Initial service		Moderate
USE		CLIMATE

Check every 1000 km

HYDRAULIC CLUTCH SYSTEM Magura

We are unable to give a standard recommendation for this component. Please contact our service department.

KTM 990 990 SUPERMOTO R (2013-2013)



COOLING SYSTEM Capacity: 2,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 30000 km/ 48 months	·

FRONT FORK WP 4860 ROMA Capacity: 732 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR WP 4618 BAVP DCC

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.