KYMCO NEW DINK NEW DINK 200I (2007 AND AFTER)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Expulsa RR 15W-50	PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50	
Change every 2000 km	1	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Expulsa RR 10W-40	PRODUCT RECOMMENDATION 2 Expulsa 10W-40	
Change every 2000 km		
use First change only		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Expulsa RR 15W-50	PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50	
Change every 300 km	<u> </u>	
use First change only		climate Moderate
PRODUCT RECOMMENDATION 1 Expulsa RR 10W-40	PRODUCT RECOMMENDATION 2 Expulsa 10W-40	
Change every 300 km		
use Second change only		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Expulsa RR 15W-50	PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50	
Change every 1000 km		
use Second change only		climate Moderate
PRODUCT RECOMMENDATION 1 Expulsa RR 10W-40	PRODUCT RECOMMENDATION 2 Expulsa 10W-40	
Change every 1000 km		,

KYMCO NEW DINK NEW DINK 2001 (2007 AND AFTER)



USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Change every 4000 km	·		
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Change every 300 km	·		
USE		CLIMATE	
Second change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 2000 km, change every 9000 km/24 months

USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Charles average 2000 lens	·	·	

Check every 3000 km

COOLING SYSTEM Capacity: 1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 5000 km/ 12 months of	hange every 10000 km	•	

Check every 5000 km/12 months, change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

KYMCO NEW DINK NEW DINK 2001 (2007 AND AFTER)



information contained herein is subject to changes without notification.