

# KYMCO PEOPLE (S) PEOPLE GT 300I (2011 AND AFTER)

**ENGINE**

Capacity: 1,5 liter (Dry fill), Capacity: 1,3 liter (Service fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 5000 km/ 6 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-50</b>		

*Change every 5000 km/ 6 months*

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 1000 km/ 1 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Expulsa RR 5W-50</b>		

*Change every 1000 km/ 1 months***FINAL REDUCTION**

Capacity: 0,23 liter (Dry fill), Capacity: 0,21 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 5000 km/ 6 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 km/ 1 months*

# KYMCO PEOPLE (S) PEOPLE GT 300I (2011 AND AFTER)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Check every 3000 km, change every 10000 km/ 12 months

## COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 3000 km, change every 10000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.