

# KYMCO XCITING XCITING 400I ABS (2012-2017)



**ENGINE SK80**  
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Check every 500 km, change every 6000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 1000 km*

**FINAL REDUCTION**  
Capacity: 200 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>

*Check every 6000 km, change every 12000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>

*Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM ABS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Drauliquid DOT 5.1</b>	

*Change every 24 months*

# KYMCO XCITING XCITING 400I ABS (2012-2017)

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*