

KYMCO YAGER YAGER 125 (2010 AND AFTER)

**ENGINE**

Capacity: 1,1 liter (Dry fill), Capacity: 0,9 liter (Service fill)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 2000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 2000 km/ 6 months***USE**

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 300 km***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 300 km***USE**

Second change only

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 1000 km/ 3 months***USE**

Second change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 10W-40****PRODUCT RECOMMENDATION 3****Expulsa 10W-40***Change every 1000 km/ 3 months*

KYMCO YAGER YAGER 125 (2010 AND AFTER)



FINAL REDUCTION

Capacity: 200 CM3 (Dry fill), Capacity: 180 CM3 (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 4000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 300 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 10000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.