

LAVERDA PHOENIX PHOENIX 200 (2002-2004)



ENGINE

Capacity: 1 liter (Initial fill), Capacity: 0,8 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50*Change every 3000 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 2

Expulsa 10W-40*Change every 3000 km*

FINAL REDUCTION FROM CVT TRANSMISSION

Capacity: 0,11 liter (Initial fill), Capacity: 0,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Check every 6000 km, change every 12000 km*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 12 months*

COOLING SYSTEM

Capacity: 0,78 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 3000 km, change every 24000 km/ 24 months*

LAVERDA PHOENIX PHOENIX 200 (2002-2004)

**FRONT FORK**

Capacity: 0,09 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.