

LINHAI LH 520 ATV ATN/ATV 520 4X4

**ENGINE LH2V70**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 3 months/ 30 hours***DIFFERENTIAL FRONT LIMITED SLIP**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours/ 12 months***FINAL REDUCTION**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 100 hours/ 12 months***GEARBOX HIGH/LOW 2/1**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 100 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 24 months/ 200 hours*

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.