

# MASH MOTORS TWO FIFTY TWO FIFTY 250

(2005-2017)



## ENGINE/TRANSMISSION

Capacity: 850 CM3

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50***Change every 3000 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 3000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 3000 km*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50***Change every 1000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 1000 km*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

# MASH MOTORS TWO FIFTY TWO FIFTY 250 (2005-2017)



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*