MBK BOOSTER BOOSTER ROCKET (1992-2010)



ENGINE + AUTOMATIC LUBRICATION CW50RSP Capacity: 1,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Tornado	Scoosynth	Maestrol	

TRANSMISSION AUTOMATIC Capacity: 0,11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Expulsa RR 10W-40	HDX 10W-40		
Check every 3000 km/ 6 months, c	hange every 12000 km/24 months	•	

HYDRAULIC BRAKE SYSTEM FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 3000 km/6 months, change every 24 months

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3	
Check every 3000 km/ 6 months, char	nge every 12000 km/ 24 months	,	

FRONT FORK Capacity: 0,08 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		
Check every 3000 km/ 6 months	,	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.