

MBK MAG MAX MAG MAX (1990-1999)**ENGINE + AUTOMATIC LUBRICATION AV10**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3

Check every 1500 km/ 3 months

COOLING SYSTEM

Capacity: 0,63 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 3000 km/ 6 months, change every 12000 km/ 24 months

FRONT FORK

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3

Check every 1500 km/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.