## **MBK OVETTO OVETTO 4T** (2008-2017)



ENGINE Capacity: 0,85 liter (Dry fill), Capacity: 0,78 liter (Service fill)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 3000 km/ 12 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 1000 km				

use Normal		climate Moderate
Expulsa RR 10W-40	HDX 10W-40	
Change every 6000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	HDX 10W-40	

HYDRAULIC BRAKE SYSTEM FRONT Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months				

## **MBK OVETTO OVETTO 4T** (2008-2017)



COOLING SYSTEM Capacity: 0,52 liter (Radiator + engine), Capacity: 0,26 liter (Reservoir)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Coolant -38 Organic NF				
Check every 6000 km/ 12 months, change every 36 mor	oths			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.