MICROCAR CARGO CARGO 505 PROGRESS (2009 AND AFTER)



ENGINE Lombardini Progress ACT (LDV Capacity: 1,4 liter (Service fill), Filter capa		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Bi-Turbo 15W-40	Emperol 5W-40
Change every 5000 km/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Bi-Turbo 15W-40	Emperol 5W-40
Change every 1000 km		

FINAL GEAR FRONT 1/1 Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 10000 km/24 months	· · · · · · · · · · · · · · · · · · ·	•

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	aax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 30000 km/ 36 months		·	

COOLING SYSTEM Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 30000 km/ 36 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.