

MICROCAR MC MC2 523 (2005-2009)

ENGINE Yanmar 2TNE68
Capacity: 1,6 liter

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30*Change every 2500 km*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30*Change every 500 km*

FINAL GEAR FRONT 1/1
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4**COOLING SYSTEM**

Capacity: 0,9 liter (Engine only)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.