

**MOTO GUZZI V SERIES V 50 II (1979-1980)****ENGINE**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**HDX 10W-40***Change every 3000 km/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**HDX 10W-40***Change every 500 km***SHAFT DRIVE**

Capacity: 0,17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140***Check every 3000 km, change every 9000 km***TRANSMISSION 5/1**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 3000 km, change every 9000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 3000 km, change every 15000 km*

**MOTO GUZZI V SERIES V 50 II (1979-1980)****FRONT FORK**

Capacity: 0,07 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Change every 21000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*