

## MOTO GUZZI V SERIES V 50 III (1981-1982)

**ENGINE**

Capacity: 2,5 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Expulsa RR 5W-50</b>  | <b>HDX 10W-40</b>        |          |

*Change every 3000 km/ 12 months*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Initial service          |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Expulsa RR 5W-50</b>  | <b>HDX 10W-40</b>        |          |

*Change every 500 km***SHAFT DRIVE**

Capacity: 0,17 liter

| USE                          |  | CLIMATE  |
|------------------------------|--|----------|
| Normal                       |  | Moderate |
| PRODUCT RECOMMENDATION 1     |  |          |
| <b>Gearlube GL-5 85W-140</b> |  |          |

*Check every 3000 km, change every 9000 km***TRANSMISSION 5/1**

Capacity: 1 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 3000 km, change every 9000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Check every 3000 km, change every 15000 km*

**MOTO GUZZI V SERIES V 50 III (1981-1982)****FRONT FORK**

Capacity: 0,06 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Change every 21000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*