## MOTO MORINI SCRAMBLER SCRAMBLER 1200 (2012 AND AFTER)



ENGINE/TRANSMISSION Moto Morini - Bialbero CorsaCorta Capacity: 3,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Check every 1000 km, change every 7500 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 1000 km				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		
Chook over 7500 km shanga ayan 15000 km/12 r	months	

Check every 7500 km, change every 15000 km/ 12 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 5.1			
Observe and 7500 km schools and 45000 km / 40 m m / 40			

Check every 7500 km, change every 15000 km/ 12 months

COOLING SYSTEM Capacity: 0-0 liter (Between min and	max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.