PRODUCT RECOMMENDATION

MV AGUSTA F4 F4 1000 R (2012-2012)

ENGINE/TRANSMISSION
Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		

Check every 1000 km, change every 6000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		

Change every 1000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 1000 km, change every 24000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 1000 km, change every 24000 km/ 24 months

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 1000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367