MV AGUSTA F4 F4 1000 (2013-2017)



ENGINE/TRANSMISSION

Capacity: 3,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| HYDRAULIC BRAKE SYSTEM | | | | |
|---------------------------|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |

Check every 1000 km, change every 24000 km/24 months

| HYDRAULIC CLUTCH SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

Check every 1000 km, change every 24000 km/24 months

| COOLING SYSTEM | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 EVO | | |
| Charles your 1000 km phanga ayan 24 mantha | | |

Check every 1000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.