PEUGEOT ELYSEO ELYSEO 2 125 (2002-2003)



| ENGINE Capacity: 1 liter, Filter capacity: 0,1 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Expulsa RR 10W-40 | Expulsa 10W-40 | HDX 10W-40 | | |

Check every 500 km, change every 10000 km

| FINAL REDUCTION Capacity: 0,12 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| 01 1 5001 1 | 100001 | <u>'</u> |

Check every 500 km, change every 10000 km

| HYDRAULIC BRAKE SYSTEM FRONT | | | |
|------------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 | |

Check every 500 km, change every 24 months

| COOLING SYSTEM Capacity: 1,5 liter | | | | |
|------------------------------------|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Coolant -38 Organic NF | Coolant -26 | | | |
| Check every 5000 km/ 12 months, c | hange every 10000 km | | | |

| FRONT FORK Capacity: 0,11 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |

PRODUCT RECOMMENDATION

PEUGEOT ELYSEO ELYSEO 2 125 (2002-2003)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.