

**PGO PA PA 125 (2006 AND AFTER)****ENGINE**

Capacity: 0,9 liter (Dry fill), Capacity: 0,8 liter (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****HDX 15W-40***Change every 5000 km***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****HDX 15W-40***Check every 500 km/ 1 months***TRANSMISSION AUTOMATIC**

Capacity: 110 CM3 (Dry fill), Capacity: 90 CM3 (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 85W-140***Check every 5000 km, change every 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 5000 km, change every 24 months***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 500 km/ 1 months*

**PGO PA PA 125 (2006 AND AFTER)****FRONT FORK**

Capacity: 80 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 5000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*