

PGO T-REX T-REX 50 (2006 AND AFTER)**ENGINE + AUTOMATIC LUBRICATION**

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	2T Super

DIFFERENTIAL REAR

Capacity: 0,33 liter (Dry fill), Filter capacity: 0,3 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS

Capacity: 0,11 liter (Dry fill), Capacity: 0,09 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 24 months

FRONT FORK

Capacity: 84 CM3 (each leg)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.